



(4) M5 X 13 LG. MAX. BOLT SUPPLIED BY CUSTOMER

SECTION A - A

OPERATING DATA:

COOLANT AND AIR SERVICE
 20,000 R.P.M. (20,000/MIN) MAX. SPEED
 995 P.S.I. (70 Kg/m²) COOLANT PRESSURE
 142 P.S.I. (10 Kg/m²) AIR PRESSURE
 160°F (121°C) MAX. TEMPERATURE

CONFIDENTIAL
 THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND IS NOT TO BE TRANSMITTED, REPRODUCED, USED OR DISCLOSED TO ANYONE WITHOUT THE WRITTEN PERMISSION OF THE DEUBLIN COMPANY.

EQUIPMENT REF:		SIZE: 2:1	REV: D
ASSY/TEST FIXTURES REQUIRED:		DATE: 06/13/02	DRW: RM
UNTOLERANCED DIMENSIONS $\pm .010$ DECIMALS AS SPECIFIED. DIMENSIONS IN [] ARE IN MILLIMETERS.		DEUBLIN COMPANY WAUKEGAN, ILLINOIS, U.S.A.	
A REMOVED NAMEPLATE AND SCREWS 014173 07/11 NR LET. REVISION EOD DATE SHH		TITLE: INTERFACE CONTROL DRAWING FOR DEUBLIN UNION 9210-002-104 NO. 9210-002-104	